**Application No.: 10/557,820** 

## Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims**

- 1. (Currently Amended) A high power light emitting diode package comprising:
- a main body having an opening to a bottom surface;
- at least two lead terminals fixed to the main body; and

at least two heat sinks of electrically and thermally conductive materials, the heat sinks being separated from each other and fixed to the main body, wherein a lower portion of each of the at least two heat sinks is exposed to the outside of the bottom surface of the main body through the opening of the main body.

- 2. (Original) The package of claim 1, wherein each of the at least two heat sinks has a reflective surface extended from an upper surface thereof.
  - 3. (Original) The package of claim 1, wherein the at least two heat sinks are a pair.
- 4. (Original) The package of claim 3, further comprising: at least one light emitting diode die mounted on upper surfaces of the at least two heat sinks, the die being directly and electrically connected to the heat sinks through a surface of the die.
- 5. (Original) The package of claim 4, further comprising: bonding wires electrically connecting the at least two lead terminals, the at least two heat sinks and the at least one light emitting diode die.

**Application No.: 10/557,820** 

6. (Original) The package of claim 4, further comprising: a lens attached to the main body, the lens enclosing the at least one light emitting diode die.

7.(Original) The package of claim 6, wherein the lens includes an optically transparent material which is directly contacted with the at least one light emitting diode die.

- 8. (Original) The package of claim 4, further comprising: a fluorescent material converting the wavelength of light emitted from the at least one light emitting diode die.
  - 9. (Original) The package of claim 1, further comprising:

light emitting diode dies mounted on the respective heat sinks, the light emitting diode dies emitting different wavelengths of light.

- 10. (Original) The package of claim 9, wherein the at least two lead terminals include: lead terminals electrically connected to the at least two heat sinks respectively; and a common lead terminal electrically connected to all of the at least two heat sinks.
- 11. (Original) The package of claim 10, further comprising: an additional heat sink; and a zener diode mounted on the additional heat sink.
- 12. (Original) The package of claim 9, wherein the light emitting diode dies include light emitting diode dies emitting a first wavelength of light, a second wavelength of light and a third wavelength of light, respectively.

**Application No.: 10/557,820** 

13. (Previously Presented) The package of claim 12, wherein the first wavelength, the second wavelength and the third wavelength are red wavelength, green wavelength and blue wavelength, respectively.

14. (Original) A light emitting diode system comprising:

the light emitting diode package according to claim 10 or claim 11; and
a controller for controlling the electric power supplied to the light emitting diode
package, wherein the controller controls the amount of the current supplied to the respective heat sinks.

15. (New) The package of claim 1, further comprising at least one septum formed in a single body along with the main body to separate the at least two heat sinks.